TECHNICAL CONCEPTS

The Neutralle Centre, Culley Court, Orton Southgate, Peterborough, Cambridgeshire, PE2 6WA. Phone: +44 (0)870 568 6824 Fax: +44 (0)870 225 8390 E-mail: info@technical-concepts.co.uk Website www.technicalconcepts.co.uk

SAFETY DATA SHEET

Page 1 of 5

Microburst Kilimanjaro Aerosol

	J	
	Revision	1
	Revision date	15-Aug-2008
1. IDENTIFICATION OF THI	E SUBSTANCE / PREPARATION AND THE COMPANY	
Product name	Microburst Kilimanjaro Aerosol Metered aerosols - Air Neutralizers.	
Intended use	Fragranced metered aerosol space sprays designed for use in proprietary automa dispensers.	ted
Company	Technical Concepts International Ltd The Neutralle Centre Culley Court Orton Southgate Peterborough PE2 6WA United Kingdom sds@technical-concepts.co.uk www.technicalconcepts.co.uk +44 (0)870 568 6824	
Telephone	+44 (0)870 568 6824	
Fax	+44 (0)870 225 8390	
Informing Department	Technical Services Department.	
2. HAZARDS IDENTIFICAT	ION	
Main hazards	Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic	

	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Classification system	The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Mixture of organic solvents, perfume and propane/iso-butane (propellant)

Hazardous ingredients				
	Conc.	CAS	EINECS	Symbols/Risk phrases
Benzyl benzoate	1-10%	120-51-4	204-402-9	Xn; R22
Ethanol	10-20%	64-17-5	200-578-6	F; R11
lsopropanol (Propan-2-ol)	1-10%	67-63-0	200-661-7	F; R11 Xi; R36 R67
Butylphenyl methylpropional	0-0.5%	80-54-6	201-289-8	Xn;R22 Xi;R43
Methyl cyclomyrcetone	1-10%	54464-57-2	259-174-3	N; R51/53
Hexyl Cinnamal	0-0.5%	101-86-0	202-983-3	Xi; R43
Ethylene Brassylate	0-0.5%	105-95-3	203-347-8	N; R51/53
D-Limonene	0-0.5%	5989-27-5	227-813-5	R10 Xi; R38 R43 N; R50/53
Linalool	0-0.5%	78-70-6	201-134-4	Xi; R38

Additional Information:

Description

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

Revision

1 15-Aug-2008

		Revision date	15-Ai
4. FIRST AID MEASURES			
Skin contact	Remove contaminated clothing. Wash all contaminated clothing before immediately with plenty of soap and water. Seek medical attention if symptoms persist.		Ť
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eye medical attention if irritation or symptoms persist.	elids open. Seek	
Inhalation	Move the exposed person to fresh air. Seek medical attention if irritation persist.	tion or symptoms	
Ingestion	Rinse mouth thoroughly. DO NOT INDUCE VOMITING. Seek medica irritation or symptoms persist.	al attention if	
5. FIRE FIGHTING MEASUR	ES		
Extinguishing media	Carbon dioxide (CO2) Alcohol resistant foam. Do NOT use water jet.		
Fire hazards	carbon oxides may be formed in fire conditions.		
Protective equipment	Wear suitable protective clothing. Wear suitable protective equipment	it.	
6. ACCIDENTAL RELEASE	MEASURES		
Personal precautions	Wear suitable protective equipment. Evacuate personnel to a safe an	ea.	
Environmental precautions	No environmental requirements.		
Clean up methods	Ensure adequate ventilation. Absorb liquid components with liquid binding material (sand, diatomite, acid binders, universal binde	rs, sawdust).	
7. HANDLING AND STORAC	3E		
Handling	Wear suitable protective equipment.		
Storage	 Ensure adequate ventilation of the working area. Keep in a cool, dry, well ventilated area. Heat will increase pressure in sealed containers. Keep away from sources of ignition - No smoking. Pressurised container. Protect from sunlight and do not expose to tell exceeding 50 °C. Do not pierce or burn, even after use. Do not spray or any incandescent material. Do not store with strong oxidising agents. Strong acids. Protect from heat and direct sunlight. Observe official regulations on storing packagings with pressurised containers. 	/ on a naked flame	¢
8. EXPOSURE CONTROLS	PERSONAL PROTECTION		
Exposure limits	Propane - Listed as an asphyxiant with no limit set.		
Ethanol		8-hr limit mg/m3: 1920 15 min limit mg/m3: -	
lsopropanol (Propan-2-ol)		8-hr limit mg/m3: 999 15 min limit mg/m3: 12	250
Engineering measures	Ensure adequate ventilation of the working area. The product does name relevant quantities of materials with critical values that have to be more workplace.	-	
Occupational exposure controls	Wash hands during breaks and at the end of the work.		
Respiratory protection	Not required, but ensure adequate ventilation when using the produc	:t.	
Hand protection	Not required when used as directed. Wash hands after handling the	product.	
Eye protection	Not required when used as directed.		
Protective equipment	Not required when used as directed.		

_ vision date

1 15-Aug-2008

	Revision
	Revision date
9. PHYSICAL AND CHEMICA	AL PROPERTIES
Description	Aerosol.
Colour	According to Product specification.
Odour	Characteristic.
Boiling point	Not applicable, as aerosol.
Flash point	Not applicable, as aerosol.
Explosive	1.8 - 19.0 vol %
Vapour pressure	4.0 ± 0.5 bar
Relative density	0.619 - 0.645 g/cm3
Melting point	Not applicable, as aerosol.
Autoignition temperature	Product is not self-igniting.
Further information	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
10. STABILITY AND REACT	νιτγ
Stability	Will not decompose if stored and used as recommended.
Conditions to avoid	Keep away from sources of ignition - No smoking. Protect from heat and direct sunlight. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Materials to avoid	Strong oxidising agents. Strong acids.
Hazardous decomposition products	carbon oxides may be formed in fire conditions.
11. TOXICOLOGICAL INFOR	MATION
Acute toxicity	No data is available on this product.

Sensitization	May cause sensitisation by skin contact.	
12. ECOLOGICAL INFORMATION		
Ecotoxicity	No data is available on this product.	
Bioaccumulation	Does not bioaccumulate.	
Further information	Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.	
13. DISPOSAL CONSIDERATIONS		
General information	Dispose of in compliance with all local and national regulations.	
Disposal of packaging	Dispose of in compliance with all local and national regulations.	

Revision

1

14. TRANSPORT INFORMATION ADR/RID UN 1950	
LIN 1950	
••••	Packing group -
Class 2	Hazard ID -
Proper Shipping AEROSO Name	ils.
Goo	1950 AEROSOLS should be placed inside the diamond shaped label. ods are classed as "Limited Quantities" and are therefore exempt from ADR ulations. Check local local legislation for domestic transport.
IMDG	
UN 1950	Packing group -
Class 2	Marine pollutant NO
EmS Code F-D S-U	
	nited Quantity" ROSOLS is required according to IMDG regulations
IATA	
UN 1950	Packing group -
Class 2	Subsidiary risk see SP63
Remarks "Lim	nited Quantity".
15. REGULATORY INFORMATION	
	product is classified in accordance with 67/548/EEC. professional use only.
	- Extremely flammable
R52	2 - Extremely flammable. 2/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the atic environment.
proc S2 - S16 S23	 Contains butylphenyl methylpropional, geraniol, hexyl cinnamal, limonene. May duce an allergic reaction. Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas.
exce	ssurised container: protect from sunlight and do not expose to temperatures eeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame iny incandescent material.

Revision Revision date 1 15-Aug-2008

16. OTHER INFORMATION		
Text of risk phrases in Section 3.	 R10 - Flammable. R11 - Highly flammable. R22 - Harmful if swallowed. R36 - Irritating to eyes. R38 - Irritating to skin. R43 - May cause sensitisation by skin contact. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67 - Vapours may cause drowsiness and dizziness. 	
Informing Department	Technical Services Department. Mr. K. Anderson.	
Data sources	Raw Material Data Sheets. EH40/2005 Occupational Exposure limits (UK)	
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.	