TECHNICAL CONCEPTS

The Neutralle Centre, Culley Court, Orton Southgate, Peterborough, Cambridgeshire, PE2 6WA.

Phone: +44 (0)870 568 6824 Fax: +44 (0)870 225 8390 E-mail: info@technical-concepts.co.uk Website www.technicalconcepts.co.uk



SAFETY DATA SHEET

Page 1 of 5

Microburst Marrakesh Aerosol

Revision

Revision date 15-Aug-2008

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Microburst Marrakesh Aerosol

Metered aerosols - Air Neutralizers.

Intended use Fragranced metered aerosol space sprays designed for use in proprietary automated

dispensers.

Company Technical Concepts International Ltd

The Neutralle Centre

Culley Court Orton Southgate Peterborough PE2 6WA United Kingdom

sds@technical-concepts.co.uk

www.technical concepts.co.uk

Telephone +44 (0)870 568 6824 **Fax** +44 (0)870 225 8390

Informing Department Technical Services Department.

2. HAZARDS IDENTIFICATION

Main hazards Extremely flammable.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Classification system The classification is in line with current EC lists. It is expanded, however, by information

from technical literature and by information furnished by supplier companies.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Description Mixture of organic solvents, perfume and propane/iso-butane (propellant)

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Ethanol	10-20%	64-17-5	200-578-6	F; R11
Isopropanol (Propan-2-ol)	1-10%	67-63-0	200-661-7	F; R11 Xi; R36 R67
Methyl cyclomyrcetone	0-0.5%	54464-57-2	259-174-3	N; R51/53
Ethylene Brassylate	0-0.5%	105-95-3	203-347-8	N; R51/53
1-[(2-tert-Butyl)cyclohexyloxy]-2-butanol	0-0.5%	139504-68-0	412-300-2	N; R51/53
Acetyl Cedrene	0-0.5%	32388-55-9	251-020-3	N; R50/53
2-Ethyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl) -2-buten-1-ol	0.5-1%	28219-61-6	248-908-8	Xi; R38 N; R50/53

Additional Information: Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

Revision 1 Revision date 15-Aug-2008

4. FIRST AID MEASURES

Skin contact Remove contaminated clothing. Wash all contaminated clothing before reuse. Wash off

immediately with plenty of soap and water. Seek medical attention if irritation or

symptoms persist.

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek

medical attention if irritation or symptoms persist.

Inhalation Move the exposed person to fresh air. Seek medical attention if irritation or symptoms

persist.

Ingestion Rinse mouth thoroughly. DO NOT INDUCE VOMITING. Seek medical attention if

irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

Extinguishing media Carbon dioxide (CO2) Alcohol resistant foam.

Do NOT use water jet.

Fire hazards carbon oxides may be formed in fire conditions.

Protective equipment Wear suitable protective clothing. Wear suitable protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Wear suitable protective equipment. Evacuate personnel to a safe area.

Environmental precautions

No environmental requirements.

Clean up methods Ensure adequate ventilation. Absorb liquid components with

liquid binding material (sand, diatomite, acid binders, universal binders, sawdust).

7. HANDLING AND STORAGE

Handling Wear suitable protective equipment.

Storage Ensure adequate ventilation of the working area.

Keep in a cool, dry, well ventilated area.

Heat will increase pressure in sealed containers. Keep away from sources of ignition - No smoking.

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame

or any incandescent material.

Do not store with strong oxidising agents. Strong acids.

Protect from heat and direct sunlight.

Observe official regulations on storing packagings with pressurised containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits Propane - Listed as an asphyxiant with no limit set.

Ethanol WEL 8-hr limit ppm: 1000 WEL 8-hr limit mg/m3: 1920

WEL 15 min limit ppm: - WEL 15 min limit mg/m3: -

 Isopropanol
 WEL 8-hr limit ppm: 400
 WEL 8-hr limit mg/m3: 999

 (Propan-2-ol)
 WEL 15 min limit ppm: 500
 WEL 15 min limit mg/m3: 1250

Engineering measures Ensure adequate ventilation of the working area. The product does not contain any

relevant quantities of materials with critical values that have to be monitored at the

workplace.

Occupational exposure

controls

Wash hands during breaks and at the end of the work.

Respiratory protection Not required, but ensure adequate ventilation when using the product.

Hand protection Not required when used as directed. Wash hands after handling the product.

Eye protection Not required when used as directed.

Protective equipment Not required when used as directed.

Revision 1
Revision date 15-Aug-2008

9. PHYSICAL AND CHEMICAL PROPERTIES

Description Aerosol.

Colour According to Product specification.

Odour Characteristic.

Boiling point Not applicable, as aerosol.

Flash point Not applicable, as aerosol.

Explosive 1.8 - 19.0 vol % Vapour pressure $4.0 \pm 0.5 \text{ bar}$

Relative density 0.619 - 0.645 g/cm3

Melting point Not applicable, as aerosol.

Autoignition temperature Product is not self-igniting.

Further information Product is not explosive. However, formation of explosive air/steam mixtures is

possible.

10. STABILITY AND REACTIVITY

Stability Will not decompose if stored and used as recommended.

Conditions to avoid Keep away from sources of ignition - No smoking.

Protect from heat and direct sunlight.

Pressurised container. Protect from sunlight and do not expose to temperatures

exceeding 50 °C.

Materials to avoid Strong oxidising agents. Strong acids.

Hazardous carbon oxides may be formed in fire conditions.

decomposition products

11. TOXICOLOGICAL INFORMATION

Acute toxicity

No data is available on this product.

Sensitization

May cause sensitisation by skin contact.

12. ECOLOGICAL INFORMATION

Ecotoxicity No data is available on this product.

Bioaccumulation Does not bioaccumulate.

Further information Do not allow undiluted product or large quantities of it to reach ground water, water

bodies or sewage system.

13. DISPOSAL CONSIDERATIONS

General information Dispose of in compliance with all local and national regulations.

Disposal of packaging Dispose of in compliance with all local and national regulations.

Revision 1 Revision date 15-Aug-2008

14. TRANSPORT INFORMATION

ADR/RID

UN 1950 Packing group - Class 2 Hazard ID -

Proper Shipping AEROSOLS.

Name

Remarks UN 1950 AEROSOLS should be placed inside the diamond shaped label.

Goods are classed as "Limited Quantities" and are therefore exempt from ADR

regulations. Check local local legislation for domestic transport.

IMDG

UN 1950 Packing group - Class 2 Marine pollutant NO

EmS Code F-D S-U

Remarks "Limited Quantity"

AEROSOLS is required according to IMDG regulations

IATA

UN 1950 Packing group -

Class 2 Subsidiary risk see SP63

Remarks "Limited Quantity".

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

For professional use only.

Symbols F+ - Extremely flammable



Risk phrases R12 - Extremely flammable.

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases S2 - Keep out of the reach of children.

S16 - Keep away from sources of ignition - No smoking.

S23 - Do not breathe gas/fumes/vapour/spray.

S51 - Use only in well-ventilated areas.

Further information Pressurised container: protect from sunlight and do not expose to temperatures

exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame

or any incandescent material.

Revision

Revision date 15-Aug-2008

16. OTHER INFORMATION

Text of risk phrases in Section 3.

R11 - Highly flammable. R36 - Irritating to eyes.

R38 - Irritating to skin.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R67 - Vapours may cause drowsiness and dizziness.

Informing Department Technical Services Department.

Mr. K. Anderson.

Data sources Raw Material Data Sheets.

EH40/2005 Occupational Exposure limits (UK)

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the

safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other

process.

*.