TECHNICAL CONCEPTS

The Neutralle Centre, Culley Court, Orton Southgate, Peterborough, Cambridgeshire, PE2 6WA. Phone: +44 (0)870 568 6824 Fax: +44 (0)870 225 8390 E-mail: info@technical-concepts.co.uk Website www.technicalconcepts.co.uk

SAFETY DATA SHEET

Page 1 of 5

Microburst Rainforest Aerosol

| | | Revision Revision date | 1 15-Aug-2008 |
|----------------------------|---|---------------------------|------------------|
| 1. IDENTIFICATION OF THE S | UBSTANCE / PREPARATION AND THE COMPANY | | |
| Product name | Microburst Rainforest Aerosol Metered aerosols - Air Neutralizers. | | |
| Intended use | Fragranced metered aerosol space sprays designed for use in prop dispensers. | prietary automated | |
| Company | Technical Concepts International Ltd The Neutralle Centre Culley Court Orton Southgate Peterborough PE2 6WA United Kingdom sds@technical-concepts.co.uk www.technicalconcepts.co.uk | | |
| Telephone | +44 (0)870 568 6824 | | |
| Fax | +44 (0)870 225 8390 | | |
| Informing Department | Technical Services Department. | | |
| 2. HAZARDS IDENTIFICATIO | ı | | |
| Main hazards | Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effect environment. | s in the aquatic | |
| Classification system | The classification is in line with current EC lists. It is expanded, how from technical literature and by information furnished by supplier co | • | on |

3. COMPOSITION / INFORMATION ON INGREDIENTS

Description

Mixture of organic solvents, perfume and propane/iso-butane (propellant)

| Hazardous ingredients | | | | |
|---|--------|-------------|-----------|---------------------------|
| | Conc. | CAS | EINECS | Symbols/Risk phrases |
| Ethanol | 10-20% | 64-17-5 | 200-578-6 | F; R11 |
| lsopropanol (Propan-2-ol) | 1-10% | 67-63-0 | 200-661-7 | F; R11 Xi; R36 R67 |
| 1-[(2-tert-Butyl)cyclohexyloxy]-2-butanol | 0-0.5% | 139504-68-0 | 412-300-2 | N; R51/53 |
| Ethylene Brassylate | 0-0.5% | 105-95-3 | 203-347-8 | N; R51/53 |
| D-Limonene | 0.5-1% | 5989-27-5 | 227-813-5 | R10 Xi; R38 R43 N; R50/53 |
| Acetyl Cedrene | 0-0.5% | 32388-55-9 | 251-020-3 | N; R50/53 |

Additional Information:

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.



Revision Revision date

1 15-Aug-2008

| | | Revision date | 15-Aug-2008 |
|-----------------------------------|---|---|-------------|
| 4. FIRST AID MEASURES | | | |
| Skin contact | Remove contaminated clothing. Wash all contaminated clothing before reuse. Wash off immediately with plenty of soap and water. Seek medical attention if irritation or symptoms persist. | | f |
| Eye contact | Rinse immediately with plenty of water for 15 minutes holding the emedical attention if irritation or symptoms persist. | yelids open. Seek | |
| Inhalation | Move the exposed person to fresh air. Seek medical attention if irrita persist. | ation or symptoms | |
| Ingestion | Rinse mouth thoroughly. DO NOT INDUCE VOMITING. Seek medi- irritation or symptoms persist. | cal attention if | |
| 5. FIRE FIGHTING MEASURES | ; | | |
| Extinguishing media | Carbon dioxide (CO2) Alcohol resistant foam. Do NOT use water jet. | | |
| Fire hazards | carbon oxides may be formed in fire conditions. | | |
| Protective equipment | Wear suitable protective clothing. Wear suitable protective equipme | ent. | |
| 6. ACCIDENTAL RELEASE ME | ASURES | | |
| Personal precautions | Wear suitable protective equipment. Evacuate personnel to a safe a | area. | |
| Environmental precautions | No environmental requirements. | | |
| Clean up methods | Ensure adequate ventilation. Absorb liquid components with liquid binding material (sand, diatomite, acid binders, universal bind | ers, sawdust). | |
| 7. HANDLING AND STORAGE | | | |
| Handling | Wear suitable protective equipment. | | |
| Storage | Ensure adequate ventilation of the working area. Keep in a cool, dry, well ventilated area. Heat will increase pressure in sealed containers. Keep away from sources of ignition - No smoking. Pressurised container. Protect from sunlight and do not expose to the exceeding 50 °C. Do not pierce or burn, even after use. Do not spra or any incandescent material. Do not store with strong oxidising agents. Strong acids. Protect from heat and direct sunlight. Observe official regulations on storing packagings with pressurised | ay on a naked flame | |
| 8. EXPOSURE CONTROLS / PI | ERSONAL PROTECTION | | |
| Exposure limits | Propane - Listed as an asphyxiant with no limit set. | | |
| Ethanol | | _ 8-hr limit mg/m3: 1920 _ 15 min limit mg/m3: - | |
| Isopropanol (Propan-2-ol) | | _ 8-hr limit mg/m3: 999 _ 15 min limit mg/m3: 12 | 50 |
| Engineering measures | Ensure adequate ventilation of the working area. The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace. | | |
| Occupational exposure controls | Wash hands during breaks and at the end of the work. | | |
| Respiratory protection | Not required, but ensure adequate ventilation when using the product. | | |
| | Not required when used as directed. Wash hands after handling the product. | | |
| Hand protection | Not required when used as directed. Wash hands after handling the | e product. | |
| Hand protection Eye protection | Not required when used as directed. Wash hands after handling the Not required when used as directed. | e product. | |

9. PHYSICAL AND CHEMICAL PROPERTIES

Revision Revision date 1 15-Aug-2008

| Description | Aerosol. | | |
|-------------------------------------|--|--|--|
| Colour | According to Product specification. | | |
| Odour | Characteristic. | | |
| Boiling point | Not applicable, as aerosol. | | |
| Flash point | Not applicable, as aerosol. | | |
| Explosive | 1.8 - 19.0 vol% | | |
| Vapour pressure | 4.0 ± 0.5 bar | | |
| Relative density | 0.619 - 0.645 g/cm3 | | |
| Melting point | Not applicable, as aerosol. | | |
| Autoignition temperature | Product is not self-igniting. | | |
| Further information | Product is not explosive. However, formation of explosive air/steam mixtures is possible. | | |
| 10. STABILITY AND REACTIVITY | | | |
| Stability | Will not decompose if stored and used as recommended. | | |
| Conditions to avoid | Keep away from sources of ignition - No smoking. Protect from heat and direct sunlight. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. | | |
| Materials to avoid | Strong oxidising agents. Strong acids. | | |
| Hazardous decomposition products | carbon oxides may be formed in fire conditions. | | |
| 11. TOXICOLOGICAL INFORM | ATION | | |
| Acute toxicity | No data is available on this product. | | |
| Sensitization | May cause sensitisation by skin contact. | | |
| 12. ECOLOGICAL INFORMATION | | | |
| Ecotoxicity | No data is available on this product. | | |
| Bioaccumulation | Does not bioaccumulate. | | |
| Further information | Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system. | | |
| 13. DISPOSAL CONSIDERATIONS | | | |
| General information | Dispose of in compliance with all local and national regulations. | | |
| Disposal of packaging | Dispose of in compliance with all local and national regulations. | | |

Revision

1

| | | Revision date | 15-Aug-2008 |
|-----------------------|---|---|-------------|
| 14. TRANSPORT INFORMA | TION | | |
| ADR/RID | | | |
| UN | 1950 | Packing group - | |
| Class | 2 | Hazard ID - | |
| Proper Shipping | AEROSOLS . | | |
| Name | | | |
| Remarks | UN 1950 AEROSOLS should be placed in | | |
| | Goods are classed as "Limited Quantities" regulations. Check local local legislation for | • | |
| IMDG | | | |
| UN | 1950 | Packing group - | |
| Class | 2 | Marine pollutant NO | |
| EmS Code | F-D S-U | - | |
| Remarks | "Limited Quantity" | | |
| | AEROSOLS is required according to IMDO | G regulations | |
| | | | |
| ΙΑΤΑ | | | |
| •••• | 1950 | Packing group - | |
| Class | 2 | Subsidiary risk see SP63 | |
| Remarks | "Limited Quantity" . | | |
| 15. REGULATORY INFORM | IATION | | |
| Labelling | The product is classified in accordance wil For professional use only. | th 67/548/EEC. | |
| Symbols | F+ - Extremely flammable | | |
| Gymbols | | | |
| | | | |
| | | | |
| Risk phrases | R12 - Extremely flammable. | | |
| | R52/53 - Harmful to aquatic organisms, ma aquatic environment. | ay cause long-term adverse effects in the | |
| Safety phrases | P10 - Contains limonene. May produce an | allergic reaction. | |
| | S2 - Keep out of the reach of children. | | |
| | S16 - Keep away from sources of ignition | - | |
| | S23 - Do not breathe gas/fumes/vapour/sp S51 - Use only in well-ventilated areas. | лау. | |
| | - | nt and do not expose to temperatures | |
| Further information | Pressunsed container, protect from suning | | |
| Further information | exceeding 50°C. Do not pierce or burn, ev or any incandescent material. | • • | ne |

Revision Revision date 1 15-Aug-2008

| 16. OTHER INFORMATION | |
|---------------------------------------|---|
| Text of risk phrases in Section 3. | R10 - Flammable. R11 - Highly flammable. R36 - Irritating to eyes. R38 - Irritating to skin. R43 - May cause sensitisation by skin contact. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67 - Vapours may cause drowsiness and dizziness. |
| Informing Department | Technical Services Department. Mr. K. Anderson. |
| Data sources | Raw Material Data Sheets. EH40/2005 Occupational Exposure limits (UK) |
| Further information | The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. |